

## Analogue Dual Relay Controller CHQ-DRC(HFP)-SCI



### Features

- ▶ Loop Powered
- ▶ Single Address
- ▶ 2 Independently Controlled Changeover relays
- ▶ Relays Contact Rated at 30 V dc at 1 amp
- ▶ Auxiliary Monitored Input
- ▶ "Smart-Fix" Housing System for flexibility
- ▶ Features an integral SCI

### Description

Model CHQ-DRC(HFP)-SCI is a Dual Relay Controller designed to provide two general-purpose relay outputs, each output can be driven separately for control of such devices as dampers or for control of plant and equipment shutdown. The monitored input can be used for local power supply fault monitoring or as a general-purpose input.

The unit features an integral short-circuit isolator and utilises simple DIL switches for reliable addressing. A back box is also available (CHQ-BACKBOX) which, when used in conjunction with the CHQ-DRC(HFP)-SCI, increases the IP rating to IP65.

<b>Specification</b>	
Order code	CHQ-DRC(HFP)-SCI
Operating voltage	17 - 41 V dc
Low Power Mode (0.75s)	170 $\mu$ A
Quiescent current	300 $\mu$ A
Current consumption	22 mA $\pm$ 20 % (polling)
Current in short-circuit	8 mA
Maximum short-circuit current (Loop)	1 A
Relay Contact Rating	30 V dc max, 1 A (resistive load)
Input E.O.L. resistor	10 k $\Omega$ , $\pm$ 5%, 0.25 W
Input threshold level	ON=470 $\Omega$ , Short cct <50 $\Omega$ , Open cct >100 k $\Omega$
Operating Temperature Range	-10°C to +50°C
Storage Temperature Range	-30°C to +60°C
Maximum Humidity	95%RH Non Condensing (at 40°C)
Weight (g)	343 (add 235 to module weight when using CHQ-BACKBOX)
Dimensions (mm)	L=157 x W=127 x D=35 (Module & Lid) D=79 (Module, Lid & CHQ-BACKBOX)
Colour and enclosure material	CHQ Module & CHQ-BACKBOX White ABS, DIN Module Green ABS, Module Lid Semi-Opaque Black ABS as standard (white version - CHQ-LID(WHT) also available)

Fire alarm control panel compatibility required for these products.

For more information on these products, please contact: