

**ACT-301**



**Actuator Details**

Operation: Forward & Reverse  
Reach (mm): 100 - 400 adjustable  
Material: Metal Body  
Size (mm): 290L x 83W x 48H  
Weight: 1.9kgs  
Wiring: 2 cores  
Voltage: 24v DC  
Current: 1.35A max  
Force: 300N

**ACT-501/ 502 / 503**



**Actuator Details**

Operation: Forward & Reverse  
Reach (mm): 800/ 600/ 450 fixed  
Material: Metal Body  
Size (mm): 765/ 650/ 575L x 80W x 50H  
Weight: 1.9 - 4kgs  
Wiring: 2 cores  
Voltage: 24v DC  
Current: 2A max  
Force: 400N

VCS-001



**Break Glass Standard Call Point**

Activation: "Smash Glass"  
Size (mm): 89W x 93H x 60D  
Material: ABS  
Colour: Yellow  
Wiring: 2 Cores  
Voltage: Max 30v DC  
Current: Max 2A  
Weight: 160g  
Switch: C NC NO

VCS-101



**Break Glass Standard Call Point**

Activation: "Smash Glass"  
Size (mm): 89W x 93H x 60D  
Material: ABS  
Colour: Orange  
Wiring: 2 Cores  
Voltage: Max 30v DC  
Current: Max 2A  
Weight: 160g  
Switch: C NC NO

VCS-003 & VCS-004



**Keyswitch Call Point**

Activation: "Keyswitch"  
Size (mm): 89W x 93H x 60D  
Material: ABS  
Colour: Yellow  
Wiring: 2 Cores (003), 3 core (004)  
Voltage: Max 30v DC  
Current: Max 2A  
Weight: 180g  
Switch: 2 pos close or 3 pos Open Close

### VCS-103 & VCS-104



#### Keyswitch Call Point

Activation: "Keyswitch"

Size (mm): 89W x 93H x 60D

Material: ABS

Colour: Orange

Wiring: 2 Cores (003), 3 core (004)

Voltage: Max 30v DC

Current: Max 2A

Weight: 180g

Switch: 2 pos close or 3 pos Open Close

### VCS-006 & VCS-007



#### Rocker Switch Call Point

Activation: "Rocker Switch "

Size (mm): 89W x 93H x 60D

Material: ABS

Colour: Yellow

Wiring: 2 Cores (003), 3 core (004)

Voltage: Max 30v DC

Current: Max 2A

Weight: 180g

Switch: 2 pos close or 3 pos Open Close

### VCS-106 & VCS-107



#### Rocker Switch Call Point

Activation: "Rocker Switch "

Size (mm): 89W x 93H x 60D

Material: ABS

Colour: Orange

Wiring: 2 Cores (003), 3 core (004)

Voltage: Max 30v DC

Current: Max 2A

Weight: 180g

Switch: 2 pos close or 3 pos Open Close

### ENS-003D (EN54 Compliant) - Switch Mode Design



#### Product Information

- Rating: 3A @ 24v dc +/- 10%
- Size: 400mmW x 300mmH x 110mmD
- Input voltage: 240AC(Std.), 230AC,
- Output voltage: 24v DC +/- 10% Typical
- Floating voltage: 27.4 – 28.0
- Standby battery type: Sealed Lead Acid
- Weight: 5kgs
- **Certification: 3rd Party CE & LVD**

### ENS-005D (EN54 Compliant) - Switch Mode Design



#### Product Information

- Rating: 5A @ 24v dc +/- 10%
- Size: 400mmW x 300mmH x 110mmD
- Input voltage: 240AC(Std.), 230AC,
- Output voltage: 24v DC +/- 10% Typical
- Floating voltage: 27.4 – 28.0
- Standby battery type: Sealed Lead Acid
- Weight: 5kgs
- **Certification: 3rd Party CE & LVD**

#### Bracket Options

BRK-301

BRK-303

BRK-304



For more information on these products, please contact us:



T: 00353 47 86274 / 00353 47 86663

E: Sales@irishsafetysystems.ie