

## MI-PSE-S2

### Digital optical detector



The MI-PSE-S2 photoelectric smoke detector has a completely new detection chamber design, the result of many years of research and development. This delivers improved responsiveness, reduced sensitivity changes caused by settling dust and reduced false alarms resulting from insect ingress and other debris. The plug-in unit uses sophisticated processing circuitry that incorporates smoothing filters to help eliminate transient environmental noise conditions that can be the cause of unwanted alarms. The devices are managed by embedded software running complex algorithms that further improve resilience to false alarms and improve detection speed.

The MI-PSE-S2 has two integral tri-colour LEDs that provide 360° local visual indication of the device status. The LEDs are programmable with static or blinking red, amber and green status indications available.

#### Specifications

- Weight: 97g (base inc)
- Dimensions (Ø x h): 102 mm x 43 mm in base B501AP
- Approved to: EN54-7, EN54-5

CPD number: 0786-CPD-20745

## MI-PSE-S2I

### Digital optical detector with isolator

## MI-FHSE-S2

### Digital 58°C thermal detector



The MI-FHSE-S2 is fixed temperature intelligent sensors employing low mass thermistors and microprocessor technology for fast response and linear temperature sensing. Their linear response allows these sensors to be used to signal temperatures over the range of 58°C (Class A1S) to 78°C (Class BS).

#### Specifications

- Weight: 88g (without base)
- Dimensions (Ø x h): 102 mm x 61 mm in base B501AP
- Approved to: EN54-5. Class A1S

CPD number: 0786-CPD-20746

## MI-FHSE-S2I

### Digital 58°C thermal detector with isolator

**MI-HTSE-S2****Digital 78°C thermal detector**

---



The MI-HTSE-S2 is fixed temperature intelligent sensors employing low mass thermistors and microprocessor technology for fast response and linear temperature sensing. Their linear response allows these sensors to be used to signal temperatures over the range of 58°C (Class A1S) to 78°C (Class BS).

**Specifications**

- Weight: 88g (without base)
- Dimensions (Ø x h): 102 mm x 61 mm in base B501AP
- Approved to: EN54-5. Class BS

**CPD number: 0786-CPD-20747****MI-HTSE-S2I****Digital 78°C thermal detector with isolator**

---

**CPD number: 0786-CPD-20741****MI-RHSE-S2****Digital R.O.R. thermal detector**

---



The MI-RHSE-S2 uses the same thermistor and microprocessor technology to provide an alarm when the rate of rise in temperature exceeds 10°C/minute (typical) or if the temperature exceeds a threshold of 58°C (Response Class A1R). With the implementation of the Advanced Protocol, any model can be software configured to be either a fixed 58°, a fixed 78° unit or a 58° with rate of rise device. For backwards compatibility and approval continuity, three separate versions continue to be available as separate part numbers.

**Specifications**

- Weight: 88g (without base)
- Dimensions (Ø x h): 102 mm x 61 mm in base B501AP
- Approved to: EN54-5. Class A1S

**CPD number: 0786-CPD-20748**

**MI-RHSE-S2I****Digital R.O.R. thermal detector with isolator**

---

**CPD number: 0786-CPD-20742****MI-PTSE-S2****Digital multi (O/T) detector**

---



The multi-criteria multi-sensor MI-PTSE-S2 Photo Thermal detector uses thermal assistance to the core photoelectric smoke detector to give enhanced false alarm immunity and faster response to a wide range of incipient fires. The plug-in unit combines two separate sensing elements that are managed by embedded software to act as a single unit. The MI-PTSE-S2 conforms to EN54-5, a 58°C fixed temperature and rate of rise thermal assistance conforming to EN54-7. The thermal detection function combines thermistor technology with a software corrected linear temperature response.

**Specifications**

- Weight: 97g (base inc)
- Dimensions (Ø x h): 102 mm x 43 mm in base B501AP
- Approved to: EN54-7, EN54-5

**CPD number: 0786-CPD-20744****MI-PTSE-S2I****Digital multi (O/T) detector with isolator**

---

**CPD number: 0786-CPD-20738****MI-PTIR-S2****Digital multi (O/T/IR) detector**

---



The MI-PTIR-S2 multi-criteria, multi-sensor Photo Thermal Infra Red detector is the environmentally friendly alternative to the ionisation detector, a technology that is now over sixty years old. The MI-PTIR-S2 offers comparable speed of response to the ionisation technology for a fast flaming fire and is less susceptible to false alarms. It can be deployed with confidence in locations where the main risk is from fast-developing flaming fires. MI-PTIR-S2 moves the goalposts in the fight against false alarms in the core detector space by delivering enhanced false alarm immunity. In addition to being an effective alternative to ionisation units, MI-PTIR-S2 offers better performance over the alternative technologies of dual angle or dual wavelength optical detectors and photo-thermal detectors.

**Specifications**

- Weight: 102g (base inc)
- Dimensions (Ø x h): 102 mm x 63 mm in base B501AP
- Approved to: EN54-7, EN54-5

**CPD number: 0786-CPD-20643****MI-PTIR-S2I****Digital multi (O/T/IR) detector with isolator**

---

**CPD number: 0786-CPD-20737**

## B501AP

## Standard mounting base



- Rugged industrial construction
- Electronic free base allowing cabling to be tested for continuity prior to the installation of the sensors
- Compact stylish design
- Easy plug in the head of base
- Tamper proof feature
- SEMS screws for easy wiring

Standard mounting base for intelligent MI200-S2 Series detectors.  
Contains address tag.

### Specifications

- |                                |   |
|--------------------------------|---|
| • Dimensions (Ø x h):          | 102 mm x 22.5 mm                              |
| • Operating temperature range: | -10°C to +60°C                                |
| • Operating humidity range:    | 10% to 93% relative humidity (non-condensing) |
| • Operating voltage:           | 15 to 32 VDC                                  |

For more information on these products, please contact us:



T: 00353 47 86274 / 00353 47 86663

E: [Sales@irishsafetysystems.ie](mailto:Sales@irishsafetysystems.ie)