



NC806CS

Overdoor Light c/w Sounder



Overview

Provides audible and visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.

Indicates Standard calls via a constant tone/constant red light and Emergency calls via a pulsing tone/pulsing red light.

Dual red LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.

Finished in tough, durable ABS plastic.

Also available as part of the NC851 Accessible Toilet Alarm kit.

Stainless steel version also available.

NC806C

Overdoor light



Overview

Provides visual indication of 800 Series Alarm calls outside bedrooms, WCs and any other area fitted with an 800 Series calling device.

Indicates Standard calls via a constant red light and Emergency calls via a pulsing red light.

Dual red LEDs and triangular diffuser make it highly visible from a distance.

Mounts on a standard UK 25mm single gang flush or surface back box.

Can also be used as an 'area indicator' at corridor junctions, staff workstations, etc.

Finished in tough, durable ABS plastic.

Also available as part of the NC851 Accessible Toilet Alarm kit.

Overdoor Lights c/w Sounders and Stainless steel version also available.

NC887D

Switchable sounder



Overview

Can be connected to any multi-zone 800 Series Call Controller or MasterIndicator Panel to increase call indication levels.

Indicates Standard calls via a constant tone and Emergency calls via a pulsing tone.

Can be switched off when not required (e.g. during night shifts to reduce call indication levels).

Can control up to two NC888D remote sounders.

When switched OFF, a red reassurance LED will illuminate as a warning.

NC888D

Remote sounder



Overview

Can be connected to any multi-zone 800 Series Call Controller, MasterIndicator Panel or Switchable Sounder to increase call indication levels.

Indicates Standard calls via a constant tone and Emergency calls via a pulsing tone.

No more than two remote sounders should be connected to the hosting device.

When connected to an NC887D Switchable Sounder, switching the NC887D off will also disable any remote sounders connected to it.

For more information on these products, please contact us:



T: 00353 47 86274 / 00353 47 86663

E: Sales@irishsafetysystems.ie