

CON456A/CX/W



Overview

Third-party certified to EN54-3 (Sounders), EN54-23 (VADs) and 17 (Isolators) by the LPCB.

Provides 'C-3-8' light distribution (min 0.4 lux over a 3 x 8m cylindrical area).

Optional white or red cap available for stand-alone use. IP21C rated

Impressive 96dB(A) sound output @ 1m.

Onboard short-circuit loop isolator.

550 μ A quiescent current.

14mA alarm current @24V DC (VAD lit, sounder on max).

Group addressing facility allows multiple devices to be operated simultaneously.

7 selectable volume levels and up to 15 selectable tone pairs.

Technical Specifications

Approvals/certifications	Certified to EN54-3, 23 & 17 by the LPCB (0832-CPR-F1115).
Protocol/compatibility	Compatible with XP95/Discovery Addressable Fire Panels.
Application/operation	Designed to be ceiling mounted - either stand-alone with a red or white cap or as part of a stacked Sounder/VAD/Detector Base combination.
VAD category & coverage	C-3-8 (15m ³ cylindrical coverage).
Flash rate & colour	0.5Hz / White.
Supply/operating voltage	17 to 28V DC (Sounder); 21 to 28V DC (Sounder/VAD).
Quiescent current	550 μ A @ 24 VDC.
Nominal SPL (Sound Pressure Level)	96dB(A) when set to tone 1.
Alarm current	14mA (VAD lit, Sounder on max).
Indicators	Polling (green LED) & Short Circuit Isolator Active (amber LED).
Product dimensions (mm)	122mm diameter x 46mm deep (not including optional XP95/Discovery detector and base).
IP Rating	IP21C (Type A).
Weight	170g.
Operating conditions/temperature	-10°C to +55°C. Max. 95% RH (Non-condensing).

For more information on these products, please contact us: